



**we leave  
a mark.**

**semket®**

Labelling systems

semket Etikettiersysteme GmbH  
Tiroler Straße 9, 3105 St. Pölten-Radlberg  
Tel: +43 (0) 2742 / 47 0 47 0  
Fax: +43 (0) 2742 / 47 0 47 90  
office@semket.com  
www.semket.com

# AG14

## The Flexible Labelling Machine



## Reliable and Efficient

[www.semket.com](http://www.semket.com)



# AG 14 - The Flexible Labelling Machine

The AG 14 is a universal label dispenser for quick, reliable and trouble-free labelling of a broad range of products.

## Characteristics

- ▶ Solid construction for the industrial use
- ▶ Left or right-hand execution
- ▶ Label feed speed from 0 - 50 m/min
- ▶ Auto-learn-mode, automatic label size detection
- ▶ Programmable in-/outputs for connection of sensors/actors or an external PLC
- ▶ RS232 Interface for parameterization via PC
- ▶ 20 memory locations for labels and parameters

## Options

- ▶ End of roll sensor, point of time for pre-warning is adjustable
- ▶ Diversity of label applicators - for customer specific requirements
- ▶ Detector for transparent labels
- ▶ Signal lamp for labeller status indication
- ▶ Speed sensor (analog or digital encoder) for synchronisation of label speed to product speed
- ▶ Powder-coated housing for highly hygienic requirements



semket AG 14 Control

## Environmental conditions

- ▶ Operating temperature 5 - 40°C
- ▶ Relative humidity 0 - 95 %, non condensing.



semket AG 14

Weight	approx. 17 kg
Operating widths	80, 120, 150, 250 or 300 mm
Labelling speed	depending on label length, up to 500 pcs/min
Nominal power	approx. 200 W
Voltage	230/115V, 50/60Hz
Feed speed	up to 50 m/min
Label stop accuracy	at 1:1 ratio +/- 0,15 mm
Dimension	approx. 500 x 700 x 320 mm
Label roll	max. 300 mm external diameter

Right of technical modification at any time reserved

A special machine program is available  
for your individual requirements.  
Take advantage of our many years of experience,  
our know-how and our already realized process innovations.